



Rating : 10A 250V AC

Fuse : 250VAC 6.3A 2.5W

Insert And Extract Force: 36kgf-6.8kgf

Terminal Strength:

Operating Life: ≥ 5000 cycles

Withstand Voltage: Between all terminals: 250VAC (50-60Hz) 1min
terminals to Base: 3750V

AC (50-60Hz) 1min
Leakage Current : 1mA

Insulation Resistance $\geq 100M\Omega$ 500V DC

Rating :

Terminal Strength: $\geq 80N$

Operating Life: 1×10^4 cycles

Withstand Voltage: Between all terminals: 1000VAC 5S
terminals to Button: 3800VAC 5S

Leakage Current : 1mA
Insulation Resistance $\geq 100M\Omega$

Contact resistance: $\leq 20m\Omega$

A4				普通公差	LANZ ELECTRONICS CO., LTD							
A3				COMMON TOLERANCE :								
A2				UP TO 5	± 0.20	单位	投影	ϕ \triangleleft mm	品名	Ac Inlet C14型	比例	Free
A1				ABOVE 5 TO 30	± 0.30	UNIT	核对应		PRODUCT NAME		SCALE	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	± 0.50	绘图	核准		型号	LZ-14-F5		
				ANGULAR	$\pm 5^\circ$	日期	核准		图号	LZ-14-F		
						DATE	APPROVAL BY		图号			
									DWG NO.			