



10W WATERPROOF LED DRIVER

- High efficiency ,long life and high reliability
- Protection:overload,over voltage,short circuit
- 100% full-load burn-in test
- 3 years warranty
- Waterproof – IP67

Specification	Model	ZA LED-10-12 B	ZA LED-10-24 B
Output	DC voltage	12V	24V
	Rated current	0.83A	0.42A
	Ripple and noise	100mVp-p	100mVp-p
	Intet stability	± 0.5%	± 0.5%
	Load stability	± 1%	± 0.5%
	Efficiency	81%	83%
Input	Voltage ADJ.range	12V ± 10%	24V ± 10%
	AC voltage range	90~264VAC 47~63Hz; 250~370VDC	
Protection	AC Inrush current	Cold-start current 30A/250V	
	Overload	105%~150% Type:pulsing hiccup shutdown Reset:auto recovery	
	Over voltage	121%~142% Rated output voltage	
Environment	Short circuit	Hiccup mode, recovers automatically after fault condition is removed	
	Setup,rise,hold up time	100ms 60ms /230VAC at full load	
	Withstand voltage	Input and output internal:1.5KvAc,input and enclosure:1.5KvAc,Output and enclosure:0.5KvAc	
Other	Isolation resistance	Input and output internal:Input and enclosure,Output and enclosure:500VDC/100MΩ	
	Working temperature and humidity	-10°C ~+50°C	
	Store temperature and humidity	-20°C ~+85°C, 10%~95%RH	
Certificate	Overall dimension	116 × 29 × 20 mm	126PCS/CARTON
	Weight	0.12Kg	
Certificate	CE EMC Authenticate	EN55022:2010 EN61000-3-2:2006+AL:2009 EN61000-3-3:2008 EN55024:2010 EN55015:2006+AL2007+2009 EN61547:2009	
	CE LVD Authenticate	EN61347-1:2008T A1:2001 EN61347-2-13:2006 EN60950-1:2006+A11:2009+A1:2010+A12:2001	
	ROHS Authenticate	EPA3050B:1996 EN1122B:2001 EPA3052:1996 EPA3060A:1996 EPA7196A:1992 EPA3540C:1996 EPA8270D:2007 IEC62321:2008	

Mechanical Specification

