

ELETE TECHNOLOGY CO.,LTD  
 億涿得股份有限公司

客户承认图

CUSTOMER(客户):		Customer Part NO(客户物品号):				
		Part Descripon(物品规格):		FF112AL=N		
Item	项目	Specification	规格值	<p>N=80mm/100MM/120MM</p>		
NO. of conductors	导体芯数	N	12			
Pitch	间距	P	1.0±0.10			
Total Pitch	全间距	PT	11±0.10			
Total Length	总长度	L	L±2			
Insulation Length	绝缘长度	IL	L-8±3			
Margin Width	边缘宽度	M	1.0±0.12			
Total Width	总宽度	W	13±0.15			
Strip Length	线口长度	S1	4±1			
Strip Length	线口长度	S2	4±1			
Reinforeing tape length	补强板长度	B1	8±2			
Reinforeing tape length	补强板长度	B2	8±2			
Slanting	线口倾斜度	A	≤0.3			
Over lap	冲孔		/			
Terminal thickness	插入厚度	t1	0.303±0.05			
Thickness insulation	线身厚度	t	0.121±0.05	Storage condition:(储存条件) Recommended(推荐)		
Conductor thickness	导体厚度	Ct	0.035±0.005	Temp: 15°C~25°C(温度15°C~25°C)Humidity: 30~60RH%(湿度30~60RH%)		
Conductor width	导体宽度	Cw	0.65±0.03	Drawing Not To Scale Hidden Lines Not Shown 图规不能以其线材比来 衡量, 隐藏线不显示		
Supporting Tapc Color	补强板颜色		(Blue)蓝色	Discharge Date 发行日期		
PET(Supporting Tapc Color)	补强板规格		0.225mm	Review Date 修订日期		
PET(Insulation)	绝缘胶规格		0.043mm (有印字)	Drawing NO 图纸编号		
PET(Insulation)	绝缘胶规格		0.043mm (无印字白色)	2018.01.11		
Rev	版本		A1	Drawing by 制图		
				Checked by 核对		
				Approved by 确认		
				Unit (单位): mm		
				iilyen		